

**NOTES:**

1. ALL DIMENSIONS AND TOLERANCES CONFORM TO ANSI Y14.5-1982.
2. DATUM PLANE [C-E] LOCATED AT MOLD PARTING LINE AND COMMENCED WITH LEAD, WHERE LEAD EXITS PLASTIC BODY AT BOTTOM OF PARTING LINE.
3. DATUMS [A-B] AND [D-E] TO BE DETERMINED WHERE CENTERLINE BETWEEN LEADS EXITS PLASTIC BODY AT DATUM PLANE [C-E].
4. TO BE DETERMINED AT SEATING PLANE [C-E].
5. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD PROTRUSION, ALLOWABLE MOLD PROTRUSION IS 0.254 MM PER SIDE. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD MISMATCH AND ARE DETERMINED AT DATUM PLANE [C-E].
6. INCLUDE MOLD MISMATCH AND ARE DETERMINED AT DATUM PLANE [C-E].
7. PACKAGE TOP DIMENSIONS ARE SMALLER THAN BOTTOM DIMENSIONS BY 0.20 MM, AND TOP OF PACKAGE WILL NOT OVERHANG BOTTOM OF PACKAGE.
8. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION, ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 MM TOTAL IN EXCESS OF THE b DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT.
9. ALL DIMENSIONS ARE IN MILLIMETERS.
10. MAXIMUM ALLOWABLE DIE THICKNESS TO BE ASSEMBLED IN THIS PKG. FAMILY IS 0.635 MM.
11. THIS DRAWING CONFORMS TO JEDEC REGISTERED OUTLINE MS-022.
12. THESE DIMENSIONS APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN 0.10 MM AND 0.25 MM FROM THE LEAD TIP.

LD CNT.	ANAM/AMKDR	JEDEC MS-022
S2	BB-2	BD
64	BD-2	BE
80	BF-2	BF

**VARIATIONS ALL DIMENSIONS IN MILLIMETERS**

L	BD			BE			BF		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	2.82	3.00	3.00	2.82	3.00	3.00	2.82	3.00	3.00
A1	0.10	0.15	0.25	0.10	0.15	0.25	0.10	0.15	0.25
Ae	2.55	2.67	2.75	2.55	2.67	2.75	2.55	2.67	2.75
D	17.20	BSC.		17.20	BSC.		17.20	BSC.	
D1	14.00	BSC.		14.00	BSC.		14.00	BSC.	
D2	12.00	BSC.		12.00	BSC.		12.35	BSC.	
D3	1.00	REF.		1.00	REF.		0.825	REF.	
E	17.20	BSC.		17.20	BSC.		17.20	BSC.	
E1	14.00	BSC.		14.00	BSC.		14.00	BSC.	
E2	12.00	BSC.		12.00	BSC.		12.35	BSC.	
E3	1.00	REF.		1.00	REF.		0.825	REF.	
L	0.73	0.88	1.03	0.73	0.88	1.03	0.73	0.88	1.03
N	52			54			80		
N1	1.00	BSC.		0.80	BSC.		0.65	BSC.	
b	0.35	0.40	0.45	0.30	0.45	0.22	0.30	0.38	0.33
b1	0.35	0.40	0.45	0.30	0.40	0.22	0.30	0.33	0.33
ccc	0.20			0.15			0.12		