

NOTES:

- 1. ALL DIMENSIONS AND TOLERANCES CONFORM TO ANSI Y14.5-1982.
- 2. DATUM PLANE [E-E] LOCATED AT MOLD PARTING LINE AND COINCIDENT WITH LEAD WHERE LEAD EXITS PLASTIC BODY AT BOTTOM OF PARTING LINE.
- 3. DATUMS [A-B] AND [D-E] TO BE DETERMINED WHERE CENTERLINE BETWEEN LEADS EXITS PLASTIC BODY AT DATUM PLANE [E-E] TO BE DETERMINED AT SEATING PLANE [C-C].
- 4. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE MOLD PROTRUSION IS 0.25 MM PER SIDE. DIMENSIONS D1 AND E1 DO INCLUDE MOLD MISMATCH AND ARE DETERMINED AT DATUM PLANE [E-E].
- 5. NUMBER OF TERMINALS.
- 6. NUMBER OF DIMENSIONS ARE SMALLER THAN BOTTOM DIMENSIONS AND TOP OF PACKAGE WILL NOT OVERHANG BOTTOM OF PACKAGE.
- 7. DIMENSION B DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 MM TOTAL IN EXCESS OF THE B DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OF THE STRAND.
- 8. CONTROL LING DIMENSION: MILLIMETER.
- 9. MAXIMUM ALLOWABLE DIE THICKNESS TO BE ASSEMBLED IN THIS PKG. PANEL IS 0.053 MM.
- 10. THIS STANDARD LINE STRANDS TO JEDEC REGISTERED OUTLINE NOT EXCEPT THE DIMENSIONS WHICH ARE 0.10 MM TO 0.36 MM RATHER THAN 0.00 MM TO 0.25 MM.

LD CNT.	ANAM/ANKOR	JEDEC
64	CA-2	CA-2
80	CB-2	CB-2
100	CC-2	CC-2
128	CD-2	CD-2

VARIATIONS ALL DIMENSIONS IN MILLIMETERS

SYMBOL	CA-2		CB-2		CC-2		CD-2	
	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.
A	3.10	3.10	3.10	3.10	3.10	3.10	3.10	3.10
A1	0.10	0.23	0.36	0.10	0.23	0.36	0.10	0.23
B	2.57	2.71	2.87	2.57	2.71	2.87	2.57	2.71
B1	23.65	23.90	24.15	23.65	23.90	24.15	23.65	23.90
B2	23.90	24.15	23.65	23.90	24.15	23.65	23.90	24.15
C	19.90	20.00	20.10	19.90	20.00	20.10	19.90	20.00
D	18.00	REF.	18.40	REF.	18.85	REF.	18.95	REF.
D1	1.00	REF.	0.80	REF.	0.58	REF.	0.75	REF.
D2	17.65	17.90	18.15	17.65	17.90	18.15	17.65	17.90
E	13.90	14.00	14.10	13.90	14.00	14.10	13.90	14.00
E1	12.00	REF.	12.00	REF.	12.35	REF.	12.5	REF.
E3	1.00	REF.	1.00	REF.	0.83	REF.	0.75	REF.
L	0.73	0.88	1.03	0.73	0.88	1.03	0.73	0.88
N	64	64	80	64	100	64	128	64
N1	1.00	BSC	0.90	BSC	0.65	BSC	0.50	BSC
N2	0.95	0.50	0.30	0.45	0.22	0.39	0.13	0.29
N3	0.95	0.40	0.30	0.35	0.40	0.33	0.13	0.20
N4	0.20	0.20	0.20	0.12	0.12	0.12	0.12	0.12
N5	19	19	24	16	30	16	38	16
N6	13	13	16	16	20	16	26	16